



Diverse Formulated Surfactants

Formulated Surfactants For Miscellaneous Industries

Nonionic/Anionic

| Trade Name | Form (30°C) | Performance | Packing (kg) | Color (30°C) | pH (1%aq.) | Specific Gravity (30°C) | Moisture (%) | Solid Content (%) |
|---------------|-------------|-------------------------------------------------------------------------------|------------------|--------------|------------|-------------------------|--------------|-------------------|
| SINOL MP | Liquid | Emulsifiers For Methyl Naphthalene, Trichlorobenzene And Orthodichlorobenzene | 200 Drum | G-12 Max. | 5-7 | 1.045-1.065 | 0.5 Max. | — |
| SINOL MP3 | Liquid | | 200 Plastic Drum | G-12 Max. | 5-7 | 1.050-1.090 | — | ④82-85 |
| SINOL MP7 | Liquid | | 100 Plastic Drum | G-8 Max. | 5-7 | 1.000-1.040 | 0.5 Max. | — |
| SINOL T4-1 | Solid | — | 20 Plastic Drum | G-5 Max. | 6.5-8 | 0.965-0.985 (50°C) | — | — |
| SINOL TSW | Liquid | Refining agent for Dyestuffs | 200 Plastic Drum | A-100 Max. | 8.0-10.0 | 0.990-1.030 | — | — |
| SINOL TWS | Liquid | Dispersing and Leveling Agent For Dispersing Dyestuffs | 100 Plastic Drum | G-12 Max. | ②6-8 | 1.065-1.085 | — | ④49-51 |
| SINOL T302 | Liquid | Lubricant For Conveyer of Producing Beverages Packaged With Glass Bottle | 200 Plastic Drum | G-5 Max. | 9.5-10.5 | 1.020-1.040 | — | ④24-28 |
| SINOL AKG-1 | Paste | Low Foaming Souring Agent With High Tolerance Of Alkali | 120 Plastic Drum | A-100 Max | — | — | 24.0-29.0 | — |
| SINOL AD-800 | Liquid | Leveling Agent For Dispersing Dyestuffs | 120 Plastic Drum | G-13 Max | — | — | 2.0 Max. | — |
| SINOL PETH456 | Paste | Wicking Finish Agent for Synthetic Fiber | 120 Plastic Drum | — | 5-7 | — | — | ④25-27 |



Diverse Formulated Surfactants

Nonionic

| Trade Name | Form (30°C) | Performance | Packing (kg) | Color (30°C) | pH (1%aq.) | Specific Gravity (30°C) | Moisture (%) | Solid Content (%) |
|-----------------|-------------|------------------------------------------------|------------------|--------------|------------|-------------------------|--------------|-------------------|
| SINOPOL T4A | Solid | Emulsifiers For Diverse Waxes | 20 Plastic Drum | G-1 Max. | 5-7 | 0.945-0.965 (60°C) | — | — |
| SINOL TNAF | Solid | Softener for Nylon | 60 Plastic Drum | — | — | — | — | — |
| SINOL ABS | Liquid | Anti-back staining Agent | 60 Plastic Drum | A-80 Max | 5.0-7.0 | — | 14-16 | — |
| SINOL TL-210G-1 | Liquid | Emulsifiers For Silicone Oil | 200 Plastic Drum | A-100 Max. | 5-7 | 1.000-1.020 | — | — |
| SINOL PRD-8 | Liquid | Thickener For Printing With Reactive Dyestuffs | 50 Plastic Drum | G-5 Max. | 5-7 | 0.850-0.870 | — | — |
| SINOL REPOX | Liquid | Emulsifier for EPOXY | 200 Plastic Drum | G-2 Max. | 4-7 | — | — | ④84-86 |
| SINOL TNAF-S2 | Liquid | — | 120 Plastic Drum | — | ⑤4.5-6.0 | — | — | ④18-22 |
| SINOL TNAF | Solid | Softener for Nylon | 60 Plastic Drum | — | — | — | — | — |
| SINOL WO-545-2 | Liquid | Emulsifiers For White Oil | 200 Plastic Drum | G-3 Max. | 5-7 | 0.950-0.970 | — | — |

Anionic

| Trade Name | Form (30°C) | Performance | Packing (kg) | Color (30°C) | pH (1%aq.) | Specific Gravity (30°C) | Moisture (%) | Solid Content (%) |
|-----------------|-------------|----------------------|------------------|--------------|------------|-------------------------|--------------|-------------------|
| SINOL MER-534-2 | Liquid | Mercerized penetrant | 120 Plastic Drum | A-200 Max. | ①8.5-10.5 | — | — | ④43-47 |

Cationic

| Trade Name | Form (30°C) | Performance | Packing (kg) | Color (30°C) | pH (1%aq.) | Specific Gravity (30°C) | Moisture (%) | Solid Content (%) |
|---------------|-------------|---------------------|--------------|--------------|------------|-------------------------|--------------|-------------------|
| SINOL TCAFN-3 | Liquid | Softener for Cotton | 200 Drum | G-8 Max. | 2-4 | — | 0.5 Max. | — |

- ① 10% aq.
- ② 2% aq.
- ③ 5% aq.
- ④ 3g/130°C/30Min.